

# AMMUNITION MEASUREMENT REPORT N° 2019-50B

on 08/01/2020

## DELIVERED TO:

UAB "Zala Arms"

Slėnio g. 8

LT-29142 Anykščiai - LITHUANIA

**SUBJECT:** Type testing

according to CIP's decisions

Manufacturing test

**TESTED SAMPLE(S)**

**CALIBER:** 12/70

**TYPE:** ZALA SPORT SLUG 28g

**LOT:** 1270118 600/9184

**SIZE:** ≤35000 pieces

*This report shows only the characteristics of the sample under test and is without prejudice to the characteristics of similar products. So it is not a product certification within the meaning of article L115-27 of the code of consumption and of the law of June 3, 1994.*

*To declare conformity or nonconformity, he was did not account of the uncertainty associated with the result.*

*The report contains 4 page(s).*

*Any reproduction of this report is permitted only in the form of full photographic facsimile unless specific written agreement of the National Proof House.*

*In case of issuance of this report electronically and/or on electronic physical media, only the report in the form of paper signed by the National Proof House is authoritative in case of dispute. This report in the form of paper is kept at the BNE for a minimum period of 20 years.*

# 1. Check of the basic package

The following indications appear on the basic packing unit:

- a) Factory name or brand of the manufacturer  Yes  No
- b) Batch identification number.  Yes  No
- c) Quantity of ammunition contained in the basic package.  Yes  No
- d) For proof cartridges: „Proof Ammunition“.  Yes  No  N/A
- e) A test marking certifying that the ammunition has been tested in accordance with C.I.P. specifications.  Yes  No
- f) Designation following TDCC denomination.  Yes  No
- High Performance Ammunition:  N/A
- g) For ammunition loaded with either lead shot or lead free shot of types A and D, an additional inscription showing clearly that they may only be fired from weapons that have been subjected to superior proof.  Yes  No  N/A
- h) For ammunition loaded with lead free shot of types B and C, an additional inscription showing clearly that they may only be fired in weapons that have been subjected to steel shot proof.  Yes  No  N/A
- i) If the diameter of the lead free shot pellets (of types B and C) in cal. 10 and cal. 12 Cartridges is greater than 4mm and in Cal. 20 Cartridges is greater than 3.25mm, an additional inscription showing clearly that these cartridges may only be fired in weapons that have been subjected to steel shot proof with barrel(s) having a choke of less than or equal to 0.5mm  Yes  No  N/A
- j) For cartridges with lead free shot of types B and C, a warning of the danger of ricochets and the need to avoid firing at hard or rigid surfaces  Yes  No  N/A
- k) In the case of re-filled cartridges, information clearly stating that they are re-filled cartridges  Yes  No  N/A
- l) For cartridges not capable of firing solid projectiles, if need be, a description of the liquid and gaseous substances discharged during firing  Yes  No  N/A
- m) For all cartridges loaded with lead free shot, the nature of the material(s) used to make the shot pellets and the type of shot; the same inscription could also be added in one of the languages used by the CIP Member States  Yes  No  N/A
- n) The commercial ammunition must be packed in suitable containers  Yes  No
- o) The basic package must be suitably closed  Yes  No
- p) Lack of cartridges of different types in the same basic package  Yes  No



## 2. Check of the existence of distinctive markings on each cartridge and, for lead free cartridges, the component parts of the cartridges

The following marks must bear on the cartridge:

<i>Admissible number of marking defects 2,3,5,8, according to lot size (double in case of type testing)</i>	<b>Number of defects</b>	<b>Number of admissible defects</b>
a) The identity of the cartridge manufacturer or the person who re-filled them or the person guaranteeing them (identification must be provided by a manufacturer's mark or a mark of origin applied in indelible fashion either to the base or the casing).	0	2
b) On the base of centrefire ammunition, the caliber in compliance with C.I.P. nomenclature. If it is impossible for technical reasons to show the caliber on the base, it may be marked in indelible fashion on the body of the casing.	0	2
c) The shell for the munitions intended for weapons with a smooth barrel of 20 gauge should be yellow in colour.	N/A	2

d) For ammunition loaded with lead shot or lead free shot the diameter in mm of the shot and the length of the cartridge case if it exceeds:  
 - 65 mm for 20 bore and above  
 - 63.5 mm for 24 bore and below.  Yes  No  N/A

e) The proof ammunition are identified either by a serrated rim, or by the colour red on the rear face of the rim, or by the whole cartridge case being red in colour, or by the words „Proof Ammunition“ coupled with the proof pressure for that caliber on the body of the cartridge case in one of the languages used by C.I.P. Member States;  Yes  No  N/A

f) The high performance ammunition for smooth bore weapons are identified either by a different color on the rear face of the rim, or by the words „Max. 1050 bar“ or „For a weapon proofed by 1320 bar“ on the body of the cartridge case in one of the languages used by C.I.P. Member States.  Yes  No  N/A

g) Ammunition meant to be fired from dust shot weapons must have different dimensions in order that such rounds may not be inserted into alarm weapons.  Yes  No  N/A

h) In the case of cartridges loaded with lead free shot, a factory marking giving the nature of the main shot material must be printed on the cartridge tube. The same inscription could also be added in one of the languages used by the CIP Member States.  Yes  No  N/A

## 3. Check of the absence of defects of the cartridges before firing

<i>Admissible number of marking defects 2,3,5,8, according to lot size (double in case of type testing)</i>	<b>Number of defects</b>	<b>Number of admissible defects</b>
a) Longitudinal fissures at the mouth, over 3 mm	0	2

Lack of the following defects:

b) Wrong caliber  Yes  No

c) Longitudinal fissures at the mouth, over 3 mm  Yes  No

d) All other longitudinal and/or transverse fissures  Yes  No

e) Rupture of the base  Yes  No



## 4. Check of the dimensions

- a) Conformity of the important dimensions from the point of view of safety :  
All ammunition sampled must conform to fixed dimension limits considered important from the point of view of safety.  Yes  No
- b) Conformity of the dimensions which define the type :  
Fixed dimension limits for type definition are checked by means of a general gauge, taking into account minimum dimensions of chambers as referred to in Addendum A. All ammunition sampled must enter smoothly into the gauge  Yes  No
- c) In the case of cartridges for alarm weapons, the total length after firing (L3) is also measured for those cartridges which were used to determine the gas pressure or energy.  Yes  No  N/A
- d) The primer is checked to verify if it does not protrude above the level of the base of the ammunition  Yes  No
- e) The lead free shot of types B and C contained in standard cartridges must have:
- Cartridges cal.12 shot diameter  $\leq 3.25\text{mm}$  (+2%)  Yes  No  N/A
  - Cartridges cal.16 shot diameter  $\leq 3.00\text{ mm}$  (+2%)  Yes  No  N/A
  - Cartridges cal. 20 shot diameter  $\leq 3.00\text{ mm}$  (+2%)  Yes  No  N/A

## 5. Check of the mean pressure, the equivalent parameters in the case of a special ammunition and, for the lead-free cartridges types B and C, of the mean velocity and the momentum.

See the herewith measurement report n° 2019-50B

All the results are conform  Yes  No

## 6. Check of the operating safety

During the shots in the pressure barrel, lack of the following defects:

- a) Escape of gases towards the rear, beyond the lock  Yes  No
- b) Seizing of the projectile, or parts thereof, within the barrel  Yes  No
- c) Tearing of the cartridge case, which remains completely or partially within the barrel  Yes  No
- d) Total stripping of the cartridge case  Yes  No
- e) Bursting of the cartridge case base  Yes  No
- f) in addition, in the case of cartridges for alarm weapons, any discharge of fragments or particles of propellant, wad, etc. from the cartridge case, which have penetrated a sheet of A2 size paper of quality 100-115 g/m<sup>2</sup> and thickness of  $0.12 \pm 0.02\text{ mm}$  mounted on a support at a distance of 1.5 m from the muzzle of the pressure measurement barrel.  Yes  No  N/A

DECISION:  ACCEPTED  REFUSED

COMMENTS:



The Director of the Banc National d'Epreuve  
**J.M.BERTHEL**



Banc National d'Epreuve  
Saint-Etienne