



Banc National d'Epreuve
Saint-Etienne

AMMUNITION MEASUREMENT REPORT N° 212-4ème présentation on 17/09/2020

DELIVERED TO:

IMI SYSTEMS

BIALIK 64 ST.

P.O.BOX 1044

Ramat Hasharon 4711001 - Israel

SUBJECT: Type testing

according to CIP's decisions

Manufacturing test

TESTED SAMPLE(S)

CALIBER: 9 mm Luger

TYPE: FMJ

LOT: 00115-20

SIZE: ≤500000 pieces

This report shows only the characteristics of the sample under test and is without prejudice to the characteristics of similar products. So it is not a product certification within the meaning of article L115-27 of the code of consumption and of the law of June 3, 1994.

To declare conformity or nonconformity, he was did not account of the uncertainty associated with the result.

The report contains 4 page(s).

Any reproduction of this report is permitted only in the form of full photographic facsimile unless specific written agreement of the National Proof House.

In case of issuance of this report electronically and/or on electronic physical media, only the report in the form of paper signed by the National Proof House is authoritative in case of dispute. This report in the form of paper is kept at the BNE for a minimum period of 20 years.

1. Check of the basic package

The following indications appear on the basic packing unit:

| | |
|--|--|
| a) Factory name or brand of the manufacturer | <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No |
| b) Batch identification number. | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No |
| c) Quantity of ammunition contained in the basic package. | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No |
| d) For proof cartridges: „Proof Ammunition“. | <input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> N/A |
| e) A test marking certifying that the ammunition has been tested in accordance with C.I.P. specifications. | <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No |
| f) Designation following TDCC denomination. | <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No |
| High Performance Ammunition: | |
| g) For ammunition loaded with either lead shot or lead free shot of types A and D, an additional inscription showing clearly that they may only be fired from weapons that have been subjected to superior proof. | <input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> N/A |
| h) For ammunition loaded with lead free shot of types B and C, an additional inscription showing clearly that they may only be fired in weapons that have been subjected to steel shot proof. | <input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> N/A |
| i) If the diameter of the lead free shot pellets (of types B and C) in cal. 10 and cal. 12 Cartridges is greater than 4mm and in Cal. 20 Cartridges is greater than 3.25mm, an additional inscription showing clearly that these cartridges may only be fired in weapons that have been subjected to steel shot proof with barrel(s) having a choke of less than or equal to 0.5mm | <input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> N/A |
| j) For cartridges with lead free shot of types B and C, a warning of the danger of ricochets and the need to avoid firing at hard or rigid surfaces | <input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> N/A |
| k) In the case of re-filled cartridges, information clearly stating that they are re-filled cartridges | <input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> N/A |
| l) For cartridges not capable of firing solid projectiles, if need be, a description of the liquid and gaseous substances discharged during firing | <input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> N/A |
| m) For all cartridges loaded with lead free shot, the nature of the material(s) used to make the shot pellets and the type of shot; the same inscription could also be added in one of the languages used by the CIP Member States | <input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> N/A |
| n) The commercial ammunition must be packed in suitable containers | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No |
| o) The basic package must be suitably closed | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No |
| p) Lack of cartridges of different types in the same basic package | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No |

2. Check of the existence of distinctive markings on each cartridge and, for lead free cartridges, the component parts of the cartridges

The following marks must bear on the cartridge:

| Admissible number of marking defects 2,3,5,8, according to lot size (double in case of type testing) | Number of defects | Number of admissible defects |
|--|-------------------|------------------------------|
| a) The identity of the cartridge manufacturer or the person who re-filled them or the person guaranteeing them (identification must be provided by a manufacturer's mark or a mark of origin applied in indelible fashion either to the base or the casing). | 0 | 2 |
| b) On the base of centrefire ammunition, the caliber in compliance with C.I.P. nomenclature. If it is impossible for technical reasons to show the caliber on the base, it may be marked in indelible fashion on the body of the casing. | 0 | 2 |
| c) The shell for the munitions intended for weapons with a smooth barrel of 20 gauge should be yellow in colour. | N/A | 2 |

d) For ammunition loaded with lead shot or lead free shot the diameter in mm of the shot and the length of the cartridge case if it exceeds: Yes No N/A

- 65 mm for 20 bore and above
- 63.5 mm for 24 bore and below.

e) The proof ammunition are identified either by a serrated rim, or by the colour red on the rear face of the rim, or by the whole cartridge case being red in colour, or by the words „Proof Ammunition“ coupled with the proof pressure for that caliber on the body of the cartridge case in one of the languages used by C.I.P. Member States; Yes No N/A

f) The high performance ammunition for smooth bore weapons are identified either by a different color on the rear face of the rim, or by the words „Max. 1050 bar“ or „For a weapon proofed by 1320 bar“ on the body of the cartridge case in one of the languages used by C.I.P. Member States. Yes No N/A

g) Ammunition meant to be fired from dust shot weapons must have different dimensions in order that such rounds may not be inserted into alarm weapons. Yes No N/A

h) In the case of cartridges loaded with lead free shot, a factory marking giving the nature of the main shot material must be printed on the cartridge tube. The same inscription could also be added in one of the languages used by the CIP Member States. Yes No N/A

3. Check of the absence of defects of the cartridges before firing

| Admissible number of marking defects 2,3,5,8, according to lot size (double in case of type testing) | Number of defects | Number of admissible defects |
|--|-------------------|------------------------------|
| a) Longitudinal fissures at the mouth, over 3 mm | 0 | 2 |

Lack of the following defects:

- b) Wrong caliber Yes No
- c) Longitudinal fissures at the mouth, over 3 mm Yes No
- d) All other longitudinal and/or transverse fissures Yes No
- e) Rupture of the base Yes No

4. Check of the dimensions

a) Conformity of the important dimensions from the point of view of safety :
All ammunition sampled must conform to fixed dimension limits considered important from the point of view of safety.

Yes No

b) Conformity of the dimensions which define the type :
Fixed dimension limits for type definition are checked by means of a general gauge, taking into account minimum dimensions of chambers as referred to in Addendum A.
All ammunition sampled must enter smoothly into the gauge

Yes No

c) In the case of cartridges for alarm weapons, the total length after firing (L3) is also measured for those cartridges which were used to determine the gas pressure or energy.

Yes No N/A

d) The primer is checked to verify if it does not protrude above the level of the base of the ammunition

Yes No

e) The lead free shot of types B and C contained in standard cartridges must have:

- Cartridges cal.12 shot diameter \leq 3.25mm (+2%)
- Cartridges cal.16 shot diameter \leq 3.00 mm (+2%)
- Cartridges cal. 20 shot diameter \leq 3.00 mm (+2%)

Yes No N/A
 Yes No N/A
 Yes No N/A

5. Check of the mean pressure, the equivalent parameters in the case of a special ammunition and, for the lead-free cartridges types B and C, of the mean velocity and the momentum.

See the herewith measurement report n° 212-4ème présentation

All the results are conform

Yes No

6. Check of the operating safety

During the shots in the pressure barrel, lack of the following defects:

- a) Escape of gases towards the rear, beyond the lock
- b) Seizing of the projectile, or parts thereof, within the barrel
- c) Tearing of the cartridge case, which remains completely or partially within the barrel
- d) Total stripping of the cartridge case
- e) Bursting of the cartridge case base
- f) in addition, in the case of cartridges for alarm weapons, any discharge of fragments or particles of propellant, wad, etc. from the cartridge case, which have penetrated a sheet of A2 size paper of quality 100-115 g/m² and thickness of 0.12 \pm 0.02 mm mounted on a support at a distance of 1.5 m from the muzzle of the pressure measurement barrel.

Yes No
 Yes No
 Yes No
 Yes No
 Yes No
 Yes No N/A

DECISION: ACCEPTED REFUSED



COMMENTS:

Add CIP marking for production.
Add Factory name or brand of the manufacturer
Add designation following TDCC denomination.

The Director of the Banc National d'Epreuve

J-M BERTHEL

P.O. Cédric BOCQUET
Quality Manager



CHAMBRE DE COMMERCE & D'INDUSTRIE
LYON METROPOLE St-Etienne Roanne
BANC NATIONAL D'EPREUVE

TYPE TESTING
N° 212 (4)

Company: IMI SYSTEMS LTD
PLANT 72
P.O.B 1044
Ramat HaSharon
ISRAEL

The Proof House decided to accord you the ratification for your batch of cartridges, caliber:

- 9 mm Luger

Consequently, you can affix on the elementary packaging of your ammunitions, the mark of control of Proof House of Saint-Etienne.

You have to make manufacturing test on **20 cartridges every year or for any new manufacturing in the Proof House of Saint-Etienne.**

This sign is a deposite trademark, a property of the Proof House of Saint-Etienne, which can be removed from you at any time, if we notice anomaly on your lots of manufacturing or if you omit to respect rules established for the manufacturing tests.

Seal of the Proof House:



The director of the Proof House:

M. BERTHEL

P.O. Cédric Bacquet
Quality Manager

Z.I. Molina La Chazotte - 5, Rue de Méons
CS 40147 - 42004 ST-ETIENNE
☎ : 04-77-25-12-06