

C.I.P.	416 Barrett	TAB.	I
		Datum	16-05-18
		Revision	25-05-13
Ursprungsland: US			
Alternative Namen: 10,4 x 83			
	PATRONE MAXI		PATRONENLAGER MINI
	Längen L1 ¹⁾ = 63.74 -0.20 L2 ¹⁾ = 71.15 -0.20 L3 ¹⁾ = 83.06 L4 = L5 = L6 = 125.73 Hülsenboden R = 2.11 R1 = 20.42 R3 = E = 6.22 E1 = 17.27 e min = 1.96 δ = 36° f = 0.69 β = 45° Pulverkammer P1 = 20.40 P2 ¹⁾ * = 18.54 -0.20 Schulterkonus α * = 50° S * = 83.62 r1 min = r2 = Hülsenhals H1 * = 11.63 H2 ¹⁾ = 11.63 Geschoss G1 ¹⁾ = 10.57 G2 = F = L3+G ¹⁾ = 92.15 Drücke (Energien) Mech. elektr. Wandler Pmax = 4400 bar PK = 5060 bar PE = 5500 bar M = 25.00 EE = 14250 Joule Verschiedene Daten Fe ¹⁾³⁾ = 0.10 delta L = 0.10		Längen L1 = 63.61 L2 = 70.94 L3 ¹⁾ = 83.44 Stoßboden R = R1 = 20.52 R2 = R3 = r = Pulverkammer E = 5.08 P1 ¹⁾ = 20.45 P2 * = 18.57 Schulterkonus α ¹⁾ * = 50° S * = 83.52 r1 max = r2 = Hülsenhals H1 * = 11.73 H2 ¹⁾ = 11.68 Geschossübergang G1 ¹⁾ * = 10.59 G ¹⁾ = 9.09 α1 = 30° h = 2.03 s * = 4.70 i ¹⁾ * = 1°30' w = Lauf F ¹⁾ * = 10.36 Z ¹⁾ = 10.57 Züge b = 4.11 N = 6 u = 304.80 Q = 86.96 mm ²
Maßstab 1:1.5		Bemerkungen: 1) Kontrolle aus Sicherheitsgründen 3) Verschlussabstand an Schulter * Grundmaße	
Maße in << mm >> Maße und Toleranzen für Messläufe siehe Anhang CR1.			