

C.I.P.**280 Rem.**

TAB.

I


Date

84-06-14

Pays d'origine: US

Révision

02-05-15

**CARTOUCHE MAXI****Longueurs**

L1 ¹⁾	=	50.78	-0.20
L2 ¹⁾	=	55.87	-0.20
L3 ¹⁾	=	64.52	
L4	=		
L5	=		
L6	=	84.58	

Culot

R	=	1.24	
R1	=	12.01	
R3	=		
E	=	3.17	
E1	=	10.39	
e min	=	0.84	
delta	=	36°	
f	=	0.38	
beta	=	35°	

Chambre à poudre

P1	=	11.97	
P2 ^{1)*}	=	11.21	-0.20

Cône de raccordement

alpha*	=	35°	
S*	=	68.56	
r1 min	=	0.64	
r2	=	2.54	

Collet

H1*	=	8.00	
H2 ¹⁾	=	8.00	

Projectile

G1 ¹⁾	=	7.23	
G2	=		
F	=		
L3+G ¹⁾	=	69.27	

Pressions (Énergies)**Méthode transducteur**

Pmax	=	4050 bar	
PK	=	4658 bar	
PE	=	5060 bar	
M	=	25.00	
EE	=	3930 Joule	

Autres indications

Fe ¹⁾	=	0.10	
delta L	=	0.14	

CHAMBRE MINI**Longueurs**

L1	=	50.61	
L2	=	55.70	
L3 ¹⁾	=	65.02	

Cuvette

R	=		
R1	=	12.06	
R2	=		
R3	=		
r	=		

Chambre à poudre

E	=	3.17	
P1 ¹⁾	=	12.00	
P2*	=	11.23	

Cône de raccordement

alpha ^{1)*}	=	34°30'	
S*	=	68.69	
r1 max	=	0.64	
r2	=	3.18	

Collet

H1*	=	8.07	
H2 ¹⁾	=	8.02	

Prise de rayures


G1 ^{1)*}	=	7.25	
G ¹⁾	=	4.75	
alpha1*	=	90°	
h	=	0.39	
s	=		
i ^{1)*}	=	1°22'34"	
w	=		

Canon

F ^{1)*}	=	7.04	
Z ¹⁾	=	7.21	

Rayures

b	=	4.06	
N	=	4	
u	=	254.00	
Q	=	40.39	mm ²



Échelle 1:1

Dimensions en << mm >>
Dimensions et tolérances pour les canons
d'épreuve: Voyez Annexe CR 1.

Notes: 1) A' contrôler pour la sécurité
* Dimensions de base