

C.I.P.**40-65 Win.**

TAB.


II

Date

17-05-17

Country of Origin: US

Revision

**CARTRIDGE MAXI****Lengths**

L1	=	31.07
L2	=	36.71
L3 ¹⁾	=	53.34
L4	=	
L5	=	
L6	=	62.74

Case Head

R ¹⁾	=	1.78	-0.25
R1	=	15.44	
R3	=		
E	=		
E1	=		
e min	=		
delta	=		
f	=	0.38	
beta	=	45°	

Powder Chamber

P1	=	12.80
P2 *	=	11.21

Junction Cone

alpha *	=	3°39'21"
S *	=	206.69
r1 min	=	
r2	=	

Collar

H1 *	=	10.85
H2 ¹⁾	=	10.83

Projectile

G1 ¹⁾	=	10.31
G2	=	
F	=	
L3+G ¹⁾	=	54.63

Pressures (Energies)**Method Transducer**

Pmax	=	2100 bar
PK	=	2415 bar
PE	=	2625 bar
M	=	25.00
EE	=	3300 Joule

Miscellaneous Dimensions

Fe ¹⁾⁴⁾	=	0.15
delta L	=	

CHAMBER MINI**Lengths**

L1	=	30.76
L2	=	36.17
L3 ¹⁾	=	53.64

Breech

R ¹⁾	=	1.78
R1	=	15.49
R2	=	
R3	=	
r	=	

Powder Chamber

E	=	
P1 ¹⁾	=	12.83
P2 *	=	11.29

Junction Cone

alpha *	=	4°01'22"
S *	=	191.49
r1 max	=	
r2	=	

Collar

H1 *	=	10.91
H2 ¹⁾	=	10.88

Commencement of Rifling


G1 ¹⁾ *	=	10.34
G ¹⁾	=	1.29
alpha 1 *	=	180°
h	=	
s	=	
i ¹⁾ *	=	4°25'58"
w	=	

Barrel

F ¹⁾ *	=	10.14
Z ¹⁾	=	10.26

Grooves

b	=	3.19
N	=	6
u	=	457.00
Q	=	81.92 mm ²



Scale 1:2.19

Dimensions in << mm >>
Dimensions and Tolerances for Proof Barrels
see Appendix CR 1.

Notes: 1) Check for safety reasons
4) Headspace on Rim
* Basic dimensions