

C.I.P.	7 mm Penna L Ursprungsland: IT	TAB. IV
		Datum 06-05-16
		Revision
	PATRONE MAXI Längen L1 = L2 = L3 ¹⁾ = 28.00 -0.25 L4 = 30.00 L5 = L6 = 41.00 Hülsenboden R ¹⁾ = 1.20 R1 = 7.95 R3 = E = 2.92 E1 = 6.80 e min = 1.15 δ = 45° f = 0.10 β = 45° Pulverkammer P1 = 7.95 P2 = Schulterkonus α = S = r1 min = r2 = Hülsenhals H1 = H2 ¹⁾ = 7.90 Geschoss G1 ^{1)*} = 7.04 G2 = 7.04 F = L3+G ¹⁾ = 32.25 Drücke (Energien) Mech. elektr. Wandler Pmax = 2750 bar PK = 3163 bar PE = 3575 bar M = 12.50 Verschiedene Daten Fe ¹⁾ = 0.30 delta L =	PATRONENLAGER MINI Längen L1 = L2 = L3 ¹⁾ = 28.00 Stoßboden R = R1 = 8.00 R2 = R3 = r = Pulverkammer E = 2.92 P1 ¹⁾ = 8.00 P2 = Schulterkonus α = S = r1 max = r2 = Hülsenhals H1 = H2 ¹⁾ = 7.98 Geschossübergang G1 ^{1)*} = 7.15 G ¹⁾ = 4.25 α1 = 180° h = s = i * = 1°57' w = Lauf F ^{1)*} = 6.86 Z ¹⁾ = 7.03 Züge b = 0.85 N = 6 u = 354.00 Q = 37.40 mm ²
Maßstab 1.5:1	Bemerkungen: 1) Kontrolle aus Sicherheitsgründen * Grundmaße	
Maße in << mm >> Maße und Toleranzen für Messläufe siehe Anhang CR 1.		